


# Glass fiber optic LCR 18-3,2-1,0-K2



■ M8 x 1 thread

Glass fiber optic - diffuse with PVC covering

## Dimensions



## Technical Data

### General specifications

Fiber optic length	l	1000 mm
Fiber optic diameter	d	5.3 mm
Adapter form		18
End piece		thread
Bending radius		min. 15 mm
Fiber bundle diameter		3.2 mm
Fiber configuration	Fv	optical seperated
Opening angle		68 °

### Approvals and certificates

Approvals		CE
-----------	--	----

### Ambient conditions

Ambient temperature		-20 ... 85 °C (-4 ... 185 °F) [Adapter]
		-20 ... 85 °C (-4 ... 185 °F) [End head and Covering]
Storage temperature		-20 ... 85 °C (-4 ... 185 °F)

### Mechanical specifications

Degree of protection		IP65
----------------------	--	------

Release date: 2022-08-04 Date of issue: 2022-08-04 Filename: 023267\_eng.pdf

**Technical Data**

Material	
Optical face	glass
Sheathing	PVC
Core	Glass fiber
End piece	Stainless steel 1.4305 / AISI 303
Adapter	PBT
Extraction force	100 N
<b>Fiber optic amplifiers</b>	
Device series	VL18LL VariKont M

## Application

**Attention:**

Fiber optics must not be twisted or kinked. Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.

