

RFID Transponder

IPC02-20P



- Battery-free code carrier
- 40 bit fix code
- Readable from both sides
- Potted housing
- Degree of protection IP67 / IP68 / IP69K


Code carrier



Application

The transponder can be read from either side.

Dimensions



Technical Data

General specifications	
Operating frequency	125 kHz
Transfer rate	2 kBit/s
Memory	
Chip Type	EM4200 Unique (EM Microelectronic)
Read cycles	unlimited
Data retention period	> 10 years
Directive conformity	
Radio equipment	
Directive 2014/53/EU	EN 300330
RoHS	
Directive 2011/65/EU (RoHS)	IEC/EN 63000
Standard conformity	
Degree of protection	EN 60529
RFID	ISO/IEC 18000-2
Ambient conditions	
Ambient temperature	-20 ... 85 °C (-4 ... 185 °F)
Storage temperature	-20 ... 85 °C (-4 ... 185 °F)

Release date: 2024-07-10 Date of issue: 2024-07-10 Filename: 199449_eng.pdf

Technical Data**Mechanical specifications**

Degree of protection	IP67 / IP68 / IP69k
Material	
Housing	PC (Polycarbonate)
Encapsulation compound	Epoxy
Installation	
In air	yes
Dimensions	
Height	2.8 mm
Height tolerance	± 0.2 mm
Diameter	19.8 mm
Diameter tolerance	± 0.2 mm
Construction type	Cylindrical