



Power supply

FB9205C


- Power supply for 100 - 230 V AC
- Suitable for the supply of FOL, field products (analyzers, level meters etc.)
- Installation in suitable enclosures in Zone 1
- Module can be exchanged under voltage (hot swap)
- Use two power supplies for redundancy
- Galvanic isolation to mains



Function

The power supply provides power for the I/O modules and com units mounted on the backplane. Input and output are galvanically isolated from each other (EN 60950-1).

Wiring Diagram



Technical Data


Supply	
Connection	wired to Ex e terminals
Rated voltage	U_r 100 ... 230 V AC
Power dissipation	7.9 W
Power consumption	max. 45 VA
Inrush current	3.4 A (10 ms)
Input	
Input frequency	50 ... 60 Hz
Output	
Voltage	24 V DC +/- 3% (Connectors 5, 12) 23 V DC +/- 3% decoupled via diode (Connectors 5, 13)
Current	1.2 A
Indicators/settings	
LED indication	LED green: supply

Technical Data

Directive conformity		
Electromagnetic compatibility		
Directive 2014/30/EU		EN 61326-1:2013
Low voltage		
Directive 2014/35/EU		EN 61010-1
Conformity		
Electromagnetic compatibility		NE 21
Degree of protection		IEC 60529
Environmental test		EN 60068-2-14
Shock resistance		EN 60068-2-27
Vibration resistance		EN 60068-2-6
Damaging gas		EN 60068-2-42
Relative humidity		EN 60068-2-78
Ambient conditions		
Ambient temperature		-20 ... 60 °C (-4 ... 140 °F)
Storage temperature		-25 ... 85 °C (-13 ... 185 °F)
Relative humidity		95 % non-condensing
Shock resistance		shock type I, shock duration 11 ms, shock amplitude 15 g, number of shocks 18
Vibration resistance		frequency range 10 ... 150 Hz; transition frequency: 57.56 Hz, amplitude/acceleration ± 0.075 mm/1 g; 10 cycles frequency range 5 ... 100 Hz; transition frequency: 13.2 Hz amplitude/acceleration ± 1 mm/0.7 g; 90 minutes at each resonance
Damaging gas		designed for operation in environmental conditions acc. to ISA-S71.04-1985, severity level G3
Mechanical specifications		
Degree of protection		IP20 (module) , a separate housing is required acc. to the system description
Mass		approx. 890 g
Dimensions		57 x 107 x 132 mm (2.2 x 4.2 x 5.2 inch)
Data for application in connection with hazardous areas		
EU-type examination certificate		PTB 97 ATEX 1074 U
Marking		Ⓜ II 2 G Ex d IIC Gb
Galvanic isolation		
Output/power supply		EN 60950-1 (safety requirement < 60 V)
Directive conformity		
Directive 2014/34/EU		EN IEC 60079-0:2018+AC:2020 EN 60079-1:2014
International approvals		
ATEX approval		PTB 97 ATEX 1074 U
General information		
System information		The module has to be mounted in appropriate backplanes (FB92**) in Zone 1, 2, or outside hazardous areas. Observe the corresponding EC-type examination certificate.
Supplementary information		EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperl-fuchs.com .

Assembly

Front view



Release date: 2025-06-20 Date of issue: 2025-06-20 Filename: 205891_eng.pdf