

# Terminal Block with Test Plug Socket KC-CTT-3GN2BU




- 2-pin spring terminal with push-in connection technology
- For KC modules of K-System
- Integrated test sockets for connection of HART communicators
- Packaging unit: 3 pieces green, 2 pieces blue

Terminal block for KC modules, 2-pin spring terminal, with test sockets

## Function

The terminal block is suitable for KSystem applications.  
The blue terminal block is used for connection of signals from or in the hazardous area.  
This terminal block has integrated test sockets for connection of HART communicators.  
The terminal block can be coded with the provided coding pins KF-CP.

## Dimensions



## Technical Data

### General specifications

Number of pins 2

### Mechanical specifications

Core cross section max. 2.5 mm<sup>2</sup>

Material

Color blue , green

Mass approx. 4 g

Dimensions 10.1 x 15 x 25.6 mm (0.4 x 0.5 x 1 inch)

Construction type spring terminal with integrated test sockets , removable

Structure one-rowed

### General information

Packing unit 5 item(s)

## Safety Information

The insulation of the removable terminal blocks protect against direct contact. The insulation conforms to a reinforced insulation acc. to EN 50178 with a rated insulation voltage of 50 V AC.

If the rated voltage greater than 50 V AC, proceed as follows:

- Switch off the voltage.
- Connect the terminal blocks or disconnect the terminal blocks.