

RFID Transponder

IPC11-20




- Battery-free data carrier
- 40 bit fixcode free programmable
- Readable from both sides
- Degree of protection IP67

Data carrier



Dimensions



Technical Data

General specifications

Operating frequency	125 kHz
Transfer rate	2 kBit/s

Memory

Chip Type	Q5 (Atmel)
EEPROM	40 Bit
Read cycles	unlimited

Directive conformity

Radio equipment	
Directive 2014/53/EU	EN 300330
RoHS	
Directive 2011/65/EU (RoHS)	IEC/EN 63000

Standard conformity

Degree of protection	EN 60529
RFID	ISO/IEC 18000-2

Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
Storage temperature	-40 ... 90 °C (-40 ... 194 °F) for 1000 hours 130 °C (266 °F) for 100 hours

Mechanical specifications

Degree of protection	IP67
----------------------	------

Release date: 2024-06-17 Date of issue: 2024-06-17 Filename: 223614_eng.pdf

Technical Data

Material		
Housing		PC (Polycarbonate)
Installation		
In air		yes
Mass		0.8 g
Dimensions		
Height		2 mm
Diameter		20 mm
Construction type		Cylindrical

Application

The transponder can be read and written from either side.