




## Inductive sensor NBB5-18GK50-E3-M

- 5 mm flush
- Extended temperature range  
-40 ... +85 °C
- E1-Type approval
- Increased noise immunity 100 V/m
- With increased sealing, protection class  
IP68 / IP69K
- Highly shock and vibration resistant



### Dimensions



### Technical Data

#### General specifications

|                              |       |                      |
|------------------------------|-------|----------------------|
| Switching function           |       | Normally closed (NC) |
| Output type                  |       | PNP                  |
| Rated operating distance     | $s_n$ | 5 mm                 |
| Installation                 |       | flush                |
| Output polarity              |       | DC                   |
| Assured operating distance   | $s_a$ | 0 ... 4.05 mm        |
| Reduction factor $r_{Al}$    |       | 0.35                 |
| Reduction factor $r_{Cu}$    |       | 0.2                  |
| Reduction factor $r_{304}$   |       | 0.8                  |
| Reduction factor $r_{Brass}$ |       | 0.4                  |
| Output type                  |       | 3-wire               |


#### Nominal ratings

|                                  |       |                            |
|----------------------------------|-------|----------------------------|
| Operating voltage                | $U_B$ | 5 ... 60 V                 |
| Switching frequency              | $f$   | 0 ... 1500 Hz              |
| Hysteresis                       | $H$   | typ. 5 %                   |
| Reverse polarity protection      |       | reverse polarity protected |
| Short-circuit protection         |       | pulsing                    |
| Inductive overvoltage protection |       | yes                        |
| Surge suppression                |       | yes                        |
| Voltage drop                     | $U_d$ | $\leq 2$ V                 |

## Technical Data

|   |           |  |
|---|-----------|--|
| Rated insulation voltage                        | $U_{BIS}$ | 60 V   |
| Operating current                               | $I_L$     | 0 ... 200 mA   |
| Off-state current                               | $I_r$     | 0 ... 0.5 mA typ. 0.1 $\mu$ A at 25 °C               |
| No-load supply current                          | $I_0$     | $\leq$ 7 mA  |
| Time delay before availability                  | $t_v$     | $\leq$ 220 ms  |
| Switching state indicator                       |           | LED, yellow  |
| <b>Functional safety related parameters</b>     |           |  |
| MTTF <sub>d</sub>                               |           | 1055 a   |
| Mission Time (T <sub>M</sub> )                  |           | 20 a   |
| Diagnostic Coverage (DC)                        |           | 0 %  |
| <b>Compliance with standards and directives</b> |           |  |
| Standard conformity                             |           |  |
| Standards                                       |           | EN IEC 60947-5-2                                     |
| <b>Approvals and certificates</b>               |           |  |
| UL approval                                     |           | cULus Listed, General Purpose, Class 2 Power Source  |
| CSA approval                                    |           | cCSAus Listed, General Purpose, Class 2 Power Source |
| CCC approval                                    |           | Certified by China Compulsory Certification (CCC)    |
| E1 Type approval                                |           | 10R-04   |
| <b>Ambient conditions</b>                       |           |  |
| Ambient temperature                             |           | -40 ... 85 °C (-40 ... 185 °F)                       |
| Storage temperature                             |           | -40 ... 85 °C (-40 ... 185 °F)                       |
| <b>Mechanical specifications</b>                |           |  |
| Connection type                                 |           | cable  |
| Housing material                                |           | PBT  |
| Sensing face                                    |           | PBT  |
| Degree of protection                            |           | IP68 / IP69K   |
| <b>Cable</b>                                    |           |  |
| Wire end ferrules                               |           | yes  |
| Cable diameter                                  |           | 6 mm $\pm$ 0.2 mm                                    |
| Bending radius                                  |           | > 6 x cable diameter                                 |
| Material  |           | PUR  |
| Color   |           | black  |
| Number of cores                                 |           | 3  |
| Core cross section                              |           | 0.75 mm <sup>2</sup>                                 |
| Length  | L         | 2 m  |
| Mass  |           | 120 g  |
| <b>Dimensions</b>                               |           |  |
| Length  |           | 58 mm  |
| Diameter  |           | 18 mm  |

## Connection Assignment



## Technical Features

Interference immunity in accordance with  
DIN ISO 11452-2: 100 V/m  
Frequency band 20 MHz up to 2 GHz

Mains-borne interference in accordance with ISO

|                   |     |     |     |     |     |     |     |
|-------------------|-----|-----|-----|-----|-----|-----|-----|
| 7637-2: Pulse     | 1   | 2a  | 2b  | 3a  | 3b  | 4   | 5   |
| Severity level    | III | III | III | III | III | III | III |
| Failure criterion | C   | A   | C   | A   | A   | A   | B   |

|                |                      |
|----------------|----------------------|
| EN 61000-4-2:  | CD: 8 kV / AD: 15 kV |
| Severity level | IV IV                |

|                |                        |
|----------------|------------------------|
| EN 61000-4-3:  | 30 V/m (80...2500 MHz) |
| Severity level | IV                     |

|                |      |
|----------------|------|
| EN 61000-4-4:  | 2 kV |
| Severity level | III  |

|                |                      |
|----------------|----------------------|
| EN 61000-4-6:  | 10 V (0.01...80 MHz) |
| Severity level | III                  |

|           |         |
|-----------|---------|
| EN 55011: | Class A |
|-----------|---------|