

# Inductive sensor


## NRB4-12GM40-A2-C



- Reduction factor = 1
- Magnetic field resistant
- Weld Immune



### Dimensions



### Technical Data

General specifications			
Switching function			complementary
Output type			PNP
Rated operating distance	$s_n$		4 mm
Installation			flush
Output polarity			switched high
Assured operating distance	$s_a$		0 ... 3.24 mm
Reduction factor $r_{Al}$			1
Reduction factor $r_{Cu}$			1
Reduction factor $r_{304}$			1
Reduction factor $r_{St37}$			1
Output type			4-wire
Nominal ratings			
Operating voltage	$U_B$		10 ... 30 V DC
Switching frequency	$f$		0 ... 2000 Hz
Hysteresis	$H$		typ. 5 %
Reverse polarity protection			reverse polarity protected
Short-circuit protection			pulsing
Voltage drop	$U_d$		$\leq 2$ V
Rated insulation voltage	$U_{BIS}$		60 V
Operating current	$I_L$		0 ... 200 mA
Off-state current	$I_r$		0 ... 0.5 mA typ. 0.1 $\mu$ A at 25 °C
No-load supply current	$I_0$		$\leq 14$ mA

Release date: 2025-06-10 Date of issue: 2025-06-10 Filename: 292518\_eng.pdf

## Technical Data

Time delay before availability	$t_v$	max. 15 ms
Constant magnetic field	B	200 mT
Alternating magnetic field	B	200 mT
Switching state indicator		all direction LED, yellow
<b>Functional safety related parameters</b>		
MTTF <sub>d</sub>		1393 a
Mission Time (T <sub>M</sub> )		20 a
Diagnostic Coverage (DC)		0 %
<b>Compliance with standards and directives</b>		
Standard conformity		
Standards		EN IEC 60947-5-2
<b>Approvals and certificates</b>		
Protection class		II
Rated insulation voltage	U <sub>i</sub>	60 V
Rated impulse withstand voltage	U <sub>imp</sub>	800 V
UL approval		cULus Listed Circuitry: Class 2 Power Source Enclosure Type Rating: Type 1 Supply/Switching Voltage: 30 V DC Output Switching Current: 200 mA
CCC approval		CCC approval / marking not required for products rated ≤36 V
<b>Ambient conditions</b>		
Ambient temperature		-40 ... 85 °C (-40 ... 185 °F)
Storage temperature		-40 ... 85 °C (-40 ... 185 °F)
<b>Mechanical specifications</b>		
Connection type		cable
Housing material		Brass, PTFE coated
Sensing face		PPS
Degree of protection		IP68 / IP69K
Cable		
Wire end ferrules		yes
Cable diameter		4.3 mm ± 0.1 mm
Bending radius		> 10 x cable diameter
Material		PUR
Color		black
Number of cores		4
Core cross section		0.34 mm <sup>2</sup>
Length	L	2 m
Mass		62 g
Dimensions		
Length		40 mm
Diameter		12 mm
<b>General information</b>		
Scope of delivery		2 self locking nuts in scope of delivery

## Connection

