



Metal protection hose CP-CDT-MS-1/4-10M


- Halogen-free
- 1/4" flexible metal conduit

1/4" flexible metal conduit 10 m

Function

The flexible metal conduit is used in conjunction with a suitable sensor adapter and a suitable cable gland to form a cable protection system for sensors. The purpose of this system is to protect the sensor wiring in harsh environments.

Dimensions









Technical Data

Ambient conditions	
Ambient temperature	- 100 ... 600 °C (212 ... 1112 °F)
Mechanical specifications	
Length	L 10 m
Bending radius	static 40 mm dynamic 50 mm
Degree of protection	IP40
Mech. capacity	
Impact resistance	Class 4, heavy (6 J) , according to EN-IEC 61386
Pressure resistance	Class 5, very heavy (4000 N) , according to EN-IEC 61386
Tensile strength	Class 4, heavy (1000 N) , according to EN-IEC 61386
Material	stainless steel 1.4301 / AISI 304

Technical Data

Mass	1190 g
General information	
Supplementary information	observe mounting instructions

Matching system components

	CP-ADP-MS-1/4-M8 5pcs	Sensor adapter for M8 sensors and 1/4" flexible metal conduit
	CP-ADP-MS-1/4-M12 5pcs	Sensor adapter for M12 sensors and 1/4" flexible metal conduit
	CP-ADP-MS-1/4-M14 5pcs	Sensor adapter for M14 sensors and 1/4" flexible metal conduit
	CP-CGL-MS-1/4-M12 5pcs	Cable gland M12 for cable diameter 1 ... 5.2 mm and 1/4" flexible metal conduit
	CP-CGL-MS-1/4-M16 5pcs	Cable gland M16 for cable diameter 1 ... 5.2 mm and 1/4" flexible metal conduit
	CG.CO.M16S.BN. C.16.K01	