




Sealing Plugs for metal Cable Glands BP.NA.M50-M63S.PA.GN.K05

- Sealing element for installation of cable glands in enclosures
- Accessory for CG.NA.* size M50 ... M63S / NPT1-1/2" ... NPT2S" cable glands metal
- Accessory for CG.EM.* size M63 / NPT2" cable glands metal
- Polyamide
- Ex e and Ex tb certified
- Suitable for operation in Zone 1, Zone 2, Zone 21 and Zone 22
- Packaging unit: 5 pieces, without accessories



Dimensions



Technical Data

Mechanical specifications	
Degree of protection	IP66 / IP68
Material	Polyamide (PA)
Finish	inherent color green
Mass	
Individual component	approx. 14 g
Packing unit	approx. 80 g
Dimensions	
Diameter (D)	37.8 mm
Outer diameter (DO)	50 mm
Length of pin (PL)	24 mm
Total length (L)	36 mm
Ambient conditions	
Ambient temperature	-60 ... 70 °C (-76 ... 158 °F)
Impact resistance	4 J
Data for application in connection with hazardous areas	
EU-type examination certificate	IMQ 14 ATEX 012X

Release date: 2024-07-18 Date of issue: 2024-07-18 Filename: 309669_eng.pdf

Technical Data

Marking	Ⓜ II 2 GD Ex e IIC Gb Ex tb IIIC Db
International approvals	
IECEX approval	IECEX IMQ 14.0004X
Conformity	
Degree of protection	EN 60529
General information	
Note	For exact reference to types and sizes of cable glands please refer to the specific datasheets
Delivery quantity	5
Scope of delivery	Sealing Plugs for metal Cable Glands Brief instructions (1 copy)
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperl-fuchs.com .