


## Stopping Plugs, Metal, Hexagon Socket Head

SP.MA.NPT1-1/4.SS.X.25.K10

- Stopping plug for unused cable entries
- Stainless Steel
- Thread NPT 1-1/4"
- Without head, installation by means of allen key
- Ex db, Ex eb and Ex tb certified
- Suitable for operation in Zone 1, Zone 2, Zone 21 and Zone 22
- Suitable for operation in Class I, Zone 1/2/22
- Suitable for operation in Class I, Division 2 when installed in accordance with NEC501.10(B)(2)
- Degree of protection IP66 / IP68, UL Type 4X
- Packaging unit: 10 pieces, without accessories



### Dimensions



Details see data table

Legend	
1	Stopping plug
KS	Key size
L	Total length
TD	Thread size
TL	Thread length

### Technical Data

#### Mechanical specifications

Thread type	NPT ANSI ASME B1.20.1
Thread size (TD)	NPT 1-1/4"
Degree of protection	IP66 / IP68 , UL Type 4X
Material	

Release date: 2024-03-19 Date of issue: 2024-03-19 Filename: 400872\_eng.pdf

## Technical Data

Finish	inherent color silver
Stopping plug	stainless steel
<b>Mass</b>	
Individual component	approx. 224 g
Packing unit	approx. 2.46 kg
<b>Dimensions</b>	
Thread length (TL)	25 mm
Total length (L)	25 mm
Key size (KS)	14 mm
<b>Tightening torque</b>	
Nut torque at enclosure (SW1)	13 Nm
<b>Ambient conditions</b>	
Ambient temperature	-60 ... 130 °C (-76 ... 266 °F)
<b>Data for application in connection with hazardous areas</b>	
EU-type examination certificate	CESI 15 ATEX 029X
Marking	Ⓜ II 2 GD Ex db IIC Gb Ex eb IIC Gb Ex tb IIC Db
<b>International approvals</b>	
UL approval	
cULus	E305142 tested to UL 50E and UL 508A CSA C22.2, No. 14-13
IECEx approval	IECEx CES 15.0006X
UKCA approval	CML 22 UKEX 1267X
CCC approval	2021312313000343
<b>Conformity</b>	
Degree of protection	EN 60529
<b>General information</b>	
Delivery quantity	10
Scope of delivery	Stopping Plugs, Metal, Hexagon Socket Head Brief instructions (1 copy)
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see <a href="http://www.pepperl-fuchs.com">www.pepperl-fuchs.com</a> .