




# Glass fiber optic LLE 04-1,6-0,5-WC3

- Chemical-resistant



Glass fiber optic - thru-beam with metal silicone covering

## Dimensions



## Technical Data

### General specifications

Fiber optic length	l	500 mm
Fiber optic diameter	d	7.3 mm
Adapter form		04
End piece		Thread / cylindrical right angle
Bending radius		min. 20 mm
Fiber bundle diameter		1.8 mm optical face: 2.5 mm <sup>2</sup>
Angle of divergence		approx. 68 °

### Approvals and certificates

Approvals		CE
-----------	--	----

### Ambient conditions

Ambient temperature		-20 ... 85 °C (-4 ... 185 °F) [Adapter] -40 ... 180 °C (-40 ... 356 °F) [End head and Covering]
Storage temperature		-20 ... 85 °C (-4 ... 185 °F)

### Mechanical specifications

Degree of protection		IP65
Material		
Optical face		glass
Sheathing		Metal-silicon
Core		Glass fiber

Release date: 2021-07-07 Date of issue: 2021-07-07 Filename: 415882\_eng.pdf

**Technical Data**

End piece	Stainless steel 1.4305 / AISI 303
Adapter	PVC
Extraction force	at probe at 20°C: 120 N
<b>Fiber optic amplifiers</b>	
Device series	MLV41-LL

## Application

**Attention:**

Fiber optics must not be twisted or kinked. Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.

