

# Retroreflective sensor

## MP2L2HD

- Harsh duty
- Withstands 1200 psi washdown
- IP69K
- Sensing range 9 m

Photoelectric Sensors; MP Series Modular

### Technical Data

#### General specifications

Sensing range	9 meters
Light source	Infrared
Light type	infrared
Polarization filter	no
Marking	CE

#### Indicators/operating means

Control elements	light on / dark on
------------------	--------------------

#### Output

Response time	≤ 10 ms
---------------	---------

#### Output 1

Output type	dependent on base selected
-------------	----------------------------

#### Standard conformity

Standards	EN 60947-5-2
-----------	--------------

#### Approvals and certificates

Approvals	CE, cULus
-----------	-----------

#### Ambient conditions

Ambient temperature	-30 ... 70 °C (-22 ... 158 °F)
Storage temperature	-55 ... 85 °C (-67 ... 185 °F)
Relative humidity	95% RH (non-condensing)
Shock resistance	50G
Vibration resistance	10G, 10 ... 500 Hz

#### Mechanical specifications

Degree of protection	IP69K
Material	
Housing	Polycarbonate
Optical face	plastic lens
Sheathing	Glass-filled acetal, Type 20
Dimensions	
Height	43.2 mm
Width	39.6 mm
Depth	52.3 mm

Release date: 2024-07-10 Date of issue: 2024-07-10 Filename: 454347\_eng.pdf