

# Fiber optic sensor MPG6HD

- Harsh duty
- Withstands 1200 psi washdown
- Sensing range dependent on fibers selected

Photoelectric Sensors; MP Series Modular

## Technical Data

### General specifications

Sensing range	Dependent on fibers selected
Light source	Infrared
Light type	infrared
Marking	CE

### Indicators/operating means

Function indicator	2 LEDs
Control elements	light on / dark on

### Output

Response time	≤ 1 ms
---------------	--------

### Output 1

Output type	dependent on base selected
-------------	----------------------------

### Standard conformity

Standards	EN 60947-5-2
-----------	--------------

### Approvals and certificates

Approvals	CE, cULus
-----------	-----------

### Ambient conditions

Ambient temperature	-30 ... 70 °C (-22 ... 158 °F)
Storage temperature	-55 ... 85 °C (-67 ... 185 °F)
Relative humidity	95% RH (non-condensing)
Shock resistance	50G
Vibration resistance	10G, 10 ... 500 Hz

### Mechanical specifications

Degree of protection	IP69K
Material	
Housing	Polycarbonate
Sheathing	Glass-filled acetal, Type 20
Dimensions	
Height	43.2 mm
Width	39.2 mm
Depth	47.2 mm

Release date: 2024-07-10 Date of issue: 2024-07-10 Filename: 454413\_eng.pdf