



# Remote Speaker Microphone

## RSM-EX01SES-Z1EUR-1SWN...AI

- Extremely long operating times with high voice volume – Up to 78 hours
- Outstanding volume and sound performance – Up to 103 dB
- Good operability, even with gloves
- Lone worker ready (with Red Button)
- Additional multi-functional buttons and a dedicated SOS button
- 2200 mAh Li-ion battery pack for a long operating time
- Linguistic feedback when changing individual modes
- Magnetic charging cable and optional charging cradle
- IoT Ready: "Custom Service Load" allows individual button settings for sending custom commands to servers and other IoT switches - e.g. to open a gate (only for Ex-Handy 10 Series)

RSM-Ex 01, wired, Zone 1, straight 3.5 mm plug for Smart-Ex 01 and Ex-Handy 09, Audio Improvement, with Red Button, version for Europe



### Technical Data

<b>General specifications</b>	
Description	Audio Improved Version
<b>Indicators/operating means</b>	
Key	Push-to-talk button operable with thick gloves Front-facing multi-function button Volume up / down with Red Button
<b>Audio data</b>	
Sound level	up to 103 dB
<b>Electrical specifications</b>	
Battery type	Li-Ion battery 3.7 V 2200 mAh 8.14 Wh
Operating duration	Stand-by time: approx. 80 h Actual use/operating time depending on use and set sound level (See table "Run times")
<b>Communication</b>	
NFC	yes
<b>Software</b>	
<b>Ambient conditions</b>	
Ambient temperature	-20 ... 55 °C (-4 ... 131 °F)
<b>Mechanical specifications</b>	
Degree of protection	IP 64 following EN/IEC 60079-0 (ATEX/ IECEx) IP 65 IP 67 following EN/IEC 60529 (industrial standard)
Connection	Socket, 3.5 mm, for headset
Connector	3.5 mm, 4-pin, straight, with lock (Smart-Ex 01 / Ex-Handy 09)
Cable	coiled
<b>Data for application in connection with hazardous areas</b>	
ATEX approval	
ATEX certificate	IBExU18ATEX1 124 X
ATEX marking	Ⓜ II 2G Ex ib IIC T4 Gb Ⓜ II 2D Ex ib IIIC T135°C Db IP64 Ⓜ I M2 Ex ib I Mb
<b>International approvals</b>	
IECEX approval	
IECEX certificate	IECEX IBE 18.0016X

Release date: 2024-08-05 Date of issue: 2024-08-05 Filename: 480984-100049\_eng.pdf

## Technical Data

IECEX marking	Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP64 Ex ib I Mb
Approved for	Europe
<b>General information</b>	
Scope of delivery	RSM-Ex Battery Charging cable Charger Safety instructions Documentation

## Accessories

Accessories for this product can be found on the internet at [www.pepperl-fuchs.com](http://www.pepperl-fuchs.com).

## Operation

### Run times\*\*

Use time in % with typical user profiles speak/hear/standby	Noisy areas with sound level above 100 dB	Noisy areas with sound level between 84 and 100 dB	Noisy areas with sound level up to 84 dB
5 / 5 / 90	-> 55 h	-> 72 h	-> 72 h
25 / 25 / 50	-> 28 h	-> 70 h	-> 71 h
50 / 50 / 0	-> 17 h	-> 67 h	-> 69 h
	Highest noise level (8/8)*	Very high noise level (4/8)*	High noise level (2/8)*
*There are 8 different volume levels possible. **determined runtimes on the Smart-Ex 01 based on RSM-Ex 01 software version V 16			