



## Tablet computer

### Tab-Ex® 05 DZ1

#### TAB-EX05-DZ1-WIFI/AIN-CS1000-NC

- Android™ 14
- Portable rugged tablet with brilliant 8" display
- Comprehensive security thanks to Samsung KNOX
- Suitable for use with gloves
- Google ARCore
- Fast data transfer via 5G connectivity
- Robust and protected against falls according to IP68 and MIL-STD-810H
- Function button for quick access

Tab-Ex 05 DZ1 (DIV 1 and Zone 1/21), Android, Wi-Fi, with camera, with microSD card, without charger, version for Europe and Northern America



### Technical Data

#### Hardware

Processor	Exynos 1380 (S5E8835) Octa-Core 4 x 2.4 GHz + 4 x 2.0 GHz 64 Bit, 5 nm
RAM	6 GB LPDDR4X
Camera	
Front camera	5 MP 1/5.0" sensor, F2.2 aperture
Main camera	13 MP 1/3.0" sensor, F1.9 aperture, autofocus, 8x digital zoom
Video recording resolution	UHD 4K (3840 x 2160) @ 30 fps
Internal data memory	128 GB UFS
Optional data memory	microSD (up to 1024 GB) 512 GB installed
Sensors	Accelerometer, Gyro Sensor, Geomagnetic Sensor, Hall Sensor, RGB Light Sensor
Speaker	yes

#### Indicators/operating means

Display	
Refresh rate	Standard (60 Hz) / Adaptive (up to 120 Hz)
Touch screen technology	Capacitive
Panel type	TFT
Screen size	20.31 cm / 8 inch
Aspect ratio	16:10
Screen resolution	1920 x 1200 (WUXGA)
Pixel density	283 ppi
Brightness	max. 600 cd/m <sup>2</sup> (nits)
Colors	16 Mio.
Screen protection	Corning® Gorilla® Glass 3
Special Features	Can be operated while wearing gloves Dark Mode, Adaptive Brightness, Eye Comfort, Screen Saver, Screen Zoom, Multi-Touch
Key	Function button, Active button

#### Electrical specifications

Battery type	Li-ion 3.8 V 5050 mAh 18.87 Wh (typically)
Operating duration	up to 14 h

#### Interface

Release date: 2025-06-30 Date of issue: 2025-06-30 Filename: 480996-100020\_eng.pdf

## Technical Data

I/O ports	USB 2.0 (Type-C)
<b>Communication</b>	
WLAN	WLAN 802.11 a/b/g (2.4 GHz), WiFi 4, 5, 6 (2.4 GHz + 5 GHz ), HE80, MIMO, 1024 QAM, WiFi Direct, Mobile Hotspot, Hotspot 2.0, Auto Hotspot
Bluetooth	Bluetooth® 5.3
GPS sensor	GPS, Glonass, Beidou, Galileo
NFC	yes
Connections	Wireless DeX
<b>Software</b>	
Operating system	Android™ 15 Android™ Enterprise Recommended verified device Google ARCore ready
<b>Cybersecurity</b>	
IT security	
Biometrics	Facial recognition
Updates	Security updates until 2032 Operating system upgrades up to Android™ 22
Mobile device protection	Samsung KNOX 3.10
<b>Ambient conditions</b>	
Ambient temperature	-20 ... 55 °C (-4 ... 131 °F)
<b>Mechanical specifications</b>	
Degree of protection	IP68 according to EN/IEC 60529 MIL-STD-810H
Mass	approx. 1122 g
Dimensions	
W x H x D	161.5 mm x 262.75 mm x 25.75 mm
<b>Data for application in connection with hazardous areas</b>	
ATEX approval	
ATEX certificate	EPS 24 ATEX 1 288 X
ATEX marking	Ⓜ II 2G Ex db ia IIC T6 Gb Ⓜ II 2D Ex tb ia IIIC T80°C Db
<b>International approvals</b>	
SGS approval	
SGS certificate	SGSNA/25/CA/00003X
SGS marking	Class I Division 1, Group A, B, C, D, T6 Class II Division 1, Group E, F, G T80C Class III T80C Ex db ia IIC T6 Gb Class I, Zone 1, AEx db ia IIC T6 Gb Zone 21, Group IIIC T80C Ambient Temperature: -20°C = Ta = +55°C
IECEX approval	
IECEX certificate	IECEX EPS 24.0082X
IECEX marking	Ex db ia IIC T6 Gb Ex ia tb IIIC T80°C Db
Approved for	Europe Northern America
<b>General information</b>	
Note	This device is not supplied with a charger.
Scope of delivery	Tab-Ex® 05 Torx T8 S Pen USB cable Documentation microSD card <b>Optional:</b> Viator Bluetooth HART Interface

## Accessories

Accessories for this product can be found on the internet at [www.pepperl-fuchs.com](http://www.pepperl-fuchs.com).