



Tablet computer

Tab-Ex® 05 DZ2

TAB-EX05-DZ2-WWANNAM-CS1000-..

- Android™ 14
- Portable rugged tablet with brilliant 8" display
- Comprehensive security thanks to Samsung KNOX
- Suitable for use with gloves
- Google ARCore
- Fast data transfer via 5G connectivity
- Robust and protected against falls according to IP68 and MIL-STD-810H
- Function button for quick access

Tab-Ex 05 DZ2 (DIV 2 and Zone 2/22), Android, WWAN (LTE) incl. Wi-Fi, with camera, with microSD card, version for Northern America



Technical Data

Hardware	
Processor	Exynos 1380 (S5E8835) Octa-Core 4 x 2.4 GHz + 4 x 2.0 GHz 64 Bit, 5 nm
RAM	6 GB LPDDR4X
Camera	
Front camera	5 MP 1/5.0" sensor, F2.2 aperture
Main camera	13 MP 1/3.0" sensor, F1.9 aperture, autofocus, 8x digital zoom
Video recording resolution	UHD 4K (3840 x 2160) @ 30 fps
Internal data memory	128 GB UFS
Sensors	Accelerometer, Gyro Sensor, Geomagnetic Sensor, Hall Sensor, RGB Light Sensor, Proximity Sensor
Speaker	yes
Indicators/operating means	
Display	
Refresh rate	Standard (60 Hz) / Adaptive (up to 120 Hz)
Touch screen technology	Capacitive
Panel type	TFT
Screen size	20.31 cm / 8 inch
Aspect ratio	16:10
Screen resolution	1920 x 1200 (WUXGA)
Pixel density	283 ppi
Brightness	max. 600 cd/m ² (nits)
Colors	16 Mio.
Screen protection	Corning® Gorilla® Glass 3
Special Features	Can be operated while wearing gloves Dark Mode, Adaptive Brightness, Eye Comfort, Screen Saver, Screen Zoom, Multi-Touch
Key	Function button, Active button
Electrical specifications	
Battery type	Li-ion 3.8 V 5050 mAh 18.87 Wh (typically)
Operating duration	up to 14 h
Interface	

Release date: 2025-06-30 Date of issue: 2025-06-30 Filename: 480997-100018_eng.pdf

Technical Data

I/O ports	USB 2.0 (Type-C) 3.5 mm headphone jack for use in hazardous locations POGO Pin
Communication	
Mobile standard	
4G	1 / 2 / 3 / 4 / 5 / 7 / 8 / 12 / 13 / 14 / 20 / 25 / 26 / 28 / 29 / 30 / 40 / 41 / 48 / 66 / 71
5G	n2 / n5 / n12 / n25 / n30 / n41 / n48 / n66 / n71 / n77 / n78
WLAN	WLAN 802.11 a/b/g (2.4 GHz), WiFi 4, 5, 6 (2.4 GHz + 5 GHz), HE80, MIMO, 1024 QAM, WiFi Direct, Mobile Hotspot, Hotspot 2.0, Auto Hotspot
Bluetooth	Bluetooth® 5.3
GPS sensor	GPS, Glonass, Beidou, Galileo
NFC	yes
Connections	Wireless DeX
SIM card	Nano (4FF) / eSIM (optional)
Software	
Operating system	Android™ 15 Android™ Enterprise Recommended verified device Google ARCore ready
Cybersecurity	
IT security	
Biometrics	Facial recognition
Updates	Security updates until 2032 Operating system upgrades up to Android™ 22
Mobile device protection	Samsung KNOX 3.10
Ambient conditions	
Ambient temperature	-20 ... 50 °C (-4 ... 122 °F)
Mechanical specifications	
Degree of protection	IP68 according to EN/IEC 60529 MIL-STD-810H
Mass	595 g
Dimensions	
W x H x D	131.8 mm x 228.7 mm x 14.5 mm
International approvals	
SGS approval	
SGS certificate	SGSNA/25/SUW/00031X
Approved for	Class I and II, Division 2, Class III, Division 1 & 2, Groups A-D, F, and G, T5 20°C ≤ Ta ≤ 50°C Zone 2 Group IIC T5 Zone 22 Group IIIB T100°C
IECEX approval	
IECEX certificate	IECEX EPS 24.0090X
IECEX marking	Ex db ia IIC T6 Gb Ex ia tb IIIC T80°C Db -20°C ≤ Ta ≤ +55°C
Approved for	Northern America
General information	
Scope of delivery	Tab-Ex® 05 Battery Ex-protective cover S Pen USB cable Charger Documentation Optional: Viator Bluetooth HART Interface

Accessories

Accessories for this product can be found on the internet at www.pepperl-fuchs.com.