



## Tablet computer

### Tab-Ex® 05 DZ2

TAB-EX05-DZ2-WWANSAU-CN1000-..

- Android™ 14
- Portable rugged tablet with brilliant 8" display
- Comprehensive security thanks to Samsung KNOX
- Suitable for use with gloves
- Google ARCore
- Fast data transfer via 5G connectivity
- Robust and protected against falls according to IP68 and MIL-STD-810H
- Function button for quick access

Tab-Ex 05 DZ2 (DIV 2 and Zone 2/22), Android, WWAN (LTE) incl. Wi-Fi, with camera, version for Saudi Arabia



## Technical Data

Hardware	
Processor	Exynos 1380 (S5E8835) Octa-Core 4 x 2.4 GHz + 4 x 2.0 GHz 64 Bit, 5 nm
RAM	6 GB LPDDR4X
Camera	
Front camera	5 MP 1/5.0" sensor, F2.2 aperture
Main camera	13 MP 1/3.0" sensor, F1.9 aperture, autofocus, 8x digital zoom
Video recording resolution	UHD 4K (3840 x 2160) @ 30 fps
Internal data memory	128 GB UFS
Optional data memory	microSD (up to 1 TB)
Sensors	Accelerometer, Gyro Sensor, Geomagnetic Sensor, Hall Sensor, RGB Light Sensor, Proximity Sensor
Speaker	yes
Indicators/operating means	
Display	
Refresh rate	Standard (60 Hz) / Adaptive (up to 120 Hz)
Touch screen technology	Capacitive
Panel type	TFT
Screen size	20.31 cm / 8 inch
Aspect ratio	16:10
Screen resolution	1920 x 1200 (WUXGA)
Pixel density	283 ppi
Brightness	max. 600 cd/m <sup>2</sup> (nits)
Colors	16 Mio.
Screen protection	Corning® Gorilla® Glass 3
Special Features	Can be operated while wearing gloves Dark Mode, Adaptive Brightness, Eye Comfort, Screen Saver, Screen Zoom, Multi-Touch
Key	Function button, Active button
Electrical specifications	
Battery type	Li-ion 3.8 V 5050 mAh 18.87 Wh (typically)
Operating duration	up to 14 h

Release date: 2025-06-30 Date of issue: 2025-06-30 Filename: 480997-100029\_eng.pdf

## Technical Data

<b>Interface</b>		
I/O ports	USB 2.0 (Type-C) 3.5 mm jack connection POGO Pin	
<b>Communication</b>		
Mobile standard		
4G	LTE FDD: B1 (2100), B2 (1900), B3 (1800), B4 (AWS), B5 (850), B7 (2600), B8 (900), B12 (700), B13 (700), B17 (700), B20 (800), B26 (850), B28 (700), B32 (1500), B66 (AWS 3), B68 (700)  LTE TDD: B38 (2600), B40 (2300), B41 (2500)  4x4 MIMO: B1 (2100), B3 (1800), B4 (AWS), B7 (2600), B66 (AWS 3), B38 (2600), B41 (2500)	
5G	Sub6 FDD: N1 (2100), N3 (1800), N5 (850), N7 (2600), N8 (900), N20 (800), N26 (850), N28 (700), N66 (AWS 3), N71 (600)  Sub6 TDD: N38 (2600), N40 (2300), N41 (2500), N77 (3700), N78 (3500)  4x4 MIMO: N1 (2100), N3 (1800), N7 (2600), N66 (AWS 3), N38 (2600), N40 (2300), N41 (2500), N77 (3700), N78 (3500)	
WLAN	WLAN 802.11 a/b/g (2.4 GHz), WiFi 4, 5, 6 (2.4 GHz + 5 GHz), HE80, MIMO, 1024 QAM, WiFi Direct, Mobile Hotspot, Hotspot 2.0, Auto Hotspot	
Bluetooth	Bluetooth® 5.3	
GPS sensor	GPS, Glonass, Beidou, Galileo	
NFC	yes	
Connections	Wireless DeX	
SIM card	Nano (4FF) / eSIM (optional)	
<b>Software</b>		
Operating system	Android™ 15 Android™ Enterprise Recommended verified device Google ARCORE ready	
<b>Cybersecurity</b>		
IT security		
Biometrics	Facial recognition	
Updates	Security updates until 2032 Operating system upgrades up to Android™ 22	
Mobile device protection	Samsung KNOX 3.10	
<b>Ambient conditions</b>		
Ambient temperature	-20 ... 55 °C (-4 ... 131 °F)	
<b>Mechanical specifications</b>		
Degree of protection	IP68 according to EN/IEC 60529 MIL-STD-810H	
Mass	595 g	
Dimensions	W x H x D 131.8 mm x 228.7 mm x 14.5 mm	
<b>Data for application in connection with hazardous areas</b>		
ATEX approval		
ATEX certificate	EPS 24 ATEX 1 257 X	
ATEX marking	Ⓜ II 3G Ex ic IIC T5 Gc Ⓜ II 3D Ex ic IIIC T85°C Dc	
<b>International approvals</b>		
IECEx approval		
IECEx certificate	IECEx EPS 24.0090X	
IECEx marking	Ex ic IIC T5 Gc Ex ic IIIC T85°C Dc	
Approved for	Saudi Arabia	
<b>General information</b>		

## Technical Data

Scope of delivery

Tab-Ex® 05  
Battery  
Ex-protective cover  
S Pen  
USB cable  
Charger  
Documentation

## Accessories

Accessories for this product can be found on the internet at [www.pepperl-fuchs.com](http://www.pepperl-fuchs.com).