



## Connecting cable

### CBL-IDMx60-D-J1-S-S18-N0

- Connection cable for corded IDM-Zx-x6x-D-\* 1-D and 2-D handheld Barcode Readers for easy connectivity of Pepperl+Fuchs VisuNet devices
- Approved for Zone 1/21 and Zone 2/22 (ATEX + IECEx)
- Compatible to DATL-IDM-DB-S-XX00-N0 (M12 female connector)
- M12 male connector to RJ50 connector with additional sealing ring

Connection cable for IDM-Zx-x6x-D-\* corded Handheld Readers

## Function

CBL-IDM160-D-\* cables allow plug-and-play connection of the corded IDM-Zx-x6x-D-\* handheld barcode readers in combination with the DATL-IDM-DB-S-XX00-N0 cable (only Serial RS-232 handheld readers and base stations are supported), SK-IDM-Zx-\* supply module and SK-IDM-Z2-J2-\* supply cable to Pepperl+Fuchs thin client / PC units, even in hazardous locations. The cable ends consist of an RJ50 (Reader) connector with additional sealing ring and a M12 male connector.

## Technical Data

### General specifications

Protocol	serial
----------	--------

### Mechanical specifications

Connection	RJ50 (reader) connector with additional sealing ring to M12 male connector
Cable	straight
Cable length	1.8 m