


Bulk Spiral Cable

SPK 3x0,5mm² BL900/200/200




- Resistant to microbes and hydrolysis
- UV resistant
- Halogen-free

Spiral Cable, PUR/PUR, 3-core black



Dimensions



Technical Data

General specifications	
Customization	sheath stripped , with wire end ferrule
Electrical specifications	
Operating voltage	U _B max. 250 V AC/DC
Conformity	
Product standard	on the basis of DIN VDE 0812
Ambient conditions	
Ambient temperature	-25 ... 80 °C (-13 ... 176 °F)
Pollution degree	3
Mechanical specifications	
Cable	according to IEC/EN 60228 (DIN VDE 0295) class 6
Sheath diameter	5 mm
Sheath color	black (similar to RAL 9005)
Number of cores	3
Core cross section	0.5 mm ²
Cores color	Core 1: white Core 2: brown Core 3: green
Core construction	64 x 0.1 mm Ø
Length	L 1.3 m extension length max. 3.6 m BL: 900 mm A1: 200 mm A2: 54 mm A3: 6 mm B1: 200 mm B2: 54 mm B3: 6 mm
Cable code	Li F 12Y 11Y 3 x 0,5
Mass	285 g
Material	
Halogen-free	yes
Cable	

Release date: 2024-07-05 Date of issue: 2024-07-05 Filename: 64314780_eng.pdf

Technical Data

Sheathing	TMPU
Cores	bare copper (Cu)
Core insulation	TPE-E
UV resistance	yes
Oil resistance	yes
Microbial resistance	yes
Hydrolysis resistance	yes

Connection Assignment



Release date: 2024-07-05 Date of issue: 2024-07-05 Filename: 64314780_eng.pdf