

Metal code bar

PXV000002M-AAMG30x500-000132



- High temperature resistance
- High mechanical stability
- Easily exchangeable
- Chemically highly resistant
- 2-colored Data Matrix codes

DataMatrix metal code bars for positioning safePXV and safePGV read heads

Function

Rugged Data Matrix metal code bars made of anodized aluminum for use on the ground in camera-based track guidance. Depending on the application, the code bars can be glued directly to the floor, or glued into special carrier profile rails. The code bars are available in modular lengths of 100, 200, and 500 mm.

Dimensions



Technical Data

General specifications

Total length 2 m

Start position 132 m

Code bar segment

Nominal segment length 500 mm

Width 30 mm

Ambient conditions

Operating temperature -40 ... 80 °C (-40 ... 176 °F)

Installation temperature 10 ... 40 °C (50 ... 104 °F)

Environmental resistance UV radiation
Humidity

Chemical resistance Oils
Grease
Fuels
Aliphatic solvents
Weak acids

Mechanical specifications

Material thickness 1 mm

Material Aluminum

Mounting type adhesive

Mass 83 g / m

Release date: 2025-06-14 Date of issue: 2025-06-14 Filename: 70127564-100478_eng.pdf

Technical Data

| | |
|-------------------------|--|
| Manufacturing tolerance | ± 1 mm/m |
| Storage | Maximum 2 years under normal storage conditions. |

Mounting

Preparing the Base Surface

1. Use clean cleaning cloths (free from lint and plasticizers) to clean the surfaces.
2. Use cleaning agents appropriate for the level of surface contamination, for example n-Heptane, ethanol, or a 50:50 mixture of isopropanol and water.
3. Clean the surface until it is completely dry and free of dust, oil, oxides, release agents, and other contaminants.
4. Ensure that the surface is dry, clean, and stable.

Adhesive Strength

| Metal | Material with high-energy surfaces | Material with low-energy surfaces |
|------------|------------------------------------|-----------------------------------|
| 33 N/25 mm | 32 N/25 mm | 31 N/25 mm |

Material thickness: 1 mm code bar + 0.13 mm adhesive

Processing Instructions

During bonding, the pressure should be as high as possible, and the temperature should be at least +10 °C. The higher the pressure and temperature, the better the adhesive will penetrate the pores of the base surface. This allows higher adhesive strength values to be achieved. It takes approx. 72 hours for the adhesive to cure.

Type Code

Structure of the type code

| | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|-----|-----|-----|-----|-----|-----|---|---|---|---|---|-----|-----|-----|---|-----|-----|-----|---|-----|-----|-----|-----|-----|-----|
| P | X | V | (1) | (1) | (1) | (1) | (1) | (1) | M | - | A | A | M | (2) | (3) | (3) | x | (4) | (4) | (4) | - | (5) | (5) | (5) | (5) | (5) | (5) |
|---|---|---|-----|-----|-----|-----|-----|-----|---|---|---|---|---|-----|-----|-----|---|-----|-----|-----|---|-----|-----|-----|-----|-----|-----|

| PXV | Sensor Type |
|-----|--------------------------|
| PXV | Position Extended Vision |

| (1) (1) (1) (1) (1) (1) | Total length of the code bar |
|-------------------------|--|
| 1 ... 100.000 | The total length of the code bar is determined by the number of individual code bar segments. The code bars can be ordered in 1 m units. |

| M | Unit |
|---|-------|
| M | Meter |

| AAM | Code bar |
|-----|-------------------------------------|
| A | Code type ECC200, symbol size 16x16 |
| A | Absolute code |
| M | Metall |

| (2) | Mounting Type |
|-----|---------------------------------|
| G | Mounting by self-adhesive back |
| H | Mounted by screwing or riveting |

| (3) (3) | Code Bar Width |
|---------|---|
| 30 | Width of the code bar in mm for mounting type G |
| 50 | Width of the code bar in mm for mounting type H |

| (4) (4) (4) | Nominal segment length of the code bars |
|-------------|--|
| 100 | Nominal segment length of the individual code bars in mm |
| 200 | Nominal segment length of the individual code bars in mm |
| 500 | Nominal segment length of the individual code bars in mm |

| (5) (5) (5) (5) (5) (5) | Start position |
|-------------------------|--------------------------------------|
| 1 ... 99.999 | Start position of the code bars in m |

Release date: 2025-06-14 Date of issue: 2025-06-14 Filename: 70127564-100478_eng.pdf