


Inductive sensor


NJ0,8-4,5-N-Y30948



■ 0.8 mm flush



Dimensions



Technical Data

General specifications

Switching function		Normally closed (NC)
Output type		NAMUR
Rated operating distance	s_n	0.8 mm
Installation		flush
Assured operating distance	s_a	0 ... 0.65 mm
Reduction factor r_{Al}		0.4
Reduction factor r_{Cu}		0.3
Reduction factor r_{304}		0.85
Output type		2-wire

Nominal ratings

Nominal voltage	U_o	8 V
Operating voltage	U_B	5 ... 25 V
Switching frequency	f	0 ... 5000 Hz
Hysteresis	H	typ. %
Current consumption		
Measuring plate not detected		≥ 3 mA at nominal voltage

Release date: 2024-05-27 Date of issue: 2024-05-29 Filename: 70133212_eng.pdf

Technical Data

Measuring plate detected	≤ 1 mA at nominal voltage	
Functional safety related parameters		
MTTF _d	1050 a	
Mission Time (T _M)	20 a	
Diagnostic Coverage (DC)	0 %	
Compliance with standards and directives		
Standard conformity		
NAMUR	EN 60947-5-6:2000 IEC 60947-5-6:1999	
Standards	EN IEC 60947-5-2	
Approvals and certificates		
IECEX approval		
Equipment protection level Gb	IECEX PTB 11.0037X	
Equipment protection level Da	IECEX PTB 11.0037X	
Equipment protection level Mb	IECEX PTB 11.0037X	
ATEX approval		
Equipment protection level Gb	PTB 00 ATEX 2048 X	
Equipment protection level Da	PTB 00 ATEX 2048 X	
UL approval	cULus Listed, General Purpose	
CML approval	on request	
Ambient conditions		
Ambient temperature	-25 ... 100 °C (-13 ... 212 °F)	
Mechanical specifications		
Connection type	cable	
Housing material	Stainless steel 1.4305 / AISI 303	
Sensing face	PBT	
Degree of protection	IP67	
Cable		
Cable diameter	3.5 mm ± 0.2 mm	
Bending radius	> 10 x cable diameter	
Material	PUR	
Core cross section	0.14 mm ²	
Length	L	2 m
Dimensions		
Length	20 mm	
Diameter	4.5 mm	
General information		
Use in the hazardous area	see instruction manuals	

Connection

