


Inductive sensor


NCN15-30GM40-N0-20M



- 15 mm non-flush
- Stainless steel housing
- NAMUR output
- Polarity reversal protected



Dimensions



Technical Data

| General specifications | | |
|-----------------------------|-------|--------------------------------------|
| Switching function | | Normally closed (NC) |
| Output type | | NAMUR |
| Rated operating distance | s_n | 15 mm |
| Installation | | non-flush |
| Assured operating distance | s_a | 0 ... 12.15 mm |
| Actual operating distance | s_r | 13.5 ... 16.5 mm typ. |
| Reduction factor r_{Al} | | 0.4 |
| Reduction factor r_{Cu} | | 0.35 |
| Reduction factor r_{304} | | 0.7 |
| Output type | | 2-wire |
| Nominal ratings | | |
| Nominal voltage | U_o | 8.2 V (R_i approx. 1 k Ω) |
| Switching frequency | f | 0 ... 150 Hz |
| Hysteresis | H | 1 ... 15 % typ. 6 % |
| Reverse polarity protection | | reverse polarity protected |
| Short-circuit protection | | yes |

Release date: 2025-06-12 Date of issue: 2025-06-15 Filename: 70133305_eng.pdf

Technical Data

| | | |
|---|---|---|
| Current consumption | | |
| Measuring plate not detected | | min. 2.2 mA |
| Measuring plate detected | | ≤ 1 mA |
| Switching state indicator | | all direction LED, yellow |
| Compliance with standards and directives | | |
| Standard conformity | | |
| NAMUR | | EN 60947-5-6:2000 IEC 60947-5-6:1999 |
| Standards | | EN IEC 60947-5-2 |
| Approvals and certificates | | |
| IECEX approval | | |
| Equipment protection level Ga | | IECEX PTB 11.0037X |
| Equipment protection level Gb | | IECEX PTB 11.0037X |
| Equipment protection level Da | | IECEX PTB 11.0037X |
| Equipment protection level Dc (tc) | | IECEX TUR 21.0018X |
| Equipment protection level Mb | | IECEX PTB 11.0037X |
| ATEX approval | | |
| Equipment protection level Ga | | PTB 00 ATEX 2048 X |
| Equipment protection level Gb | | PTB 00 ATEX 2048 X |
| Equipment protection level Da | | PTB 00 ATEX 2048 X |
| Equipment protection level Dc (tc) | | TÜV 20 ATEX 8524 X |
| UL approval | | |
| Ordinary Location | | E87056 |
| Hazardous Location | | E501628 |
| Control drawing | | 116-0452 |
| CCC approval | | |
| Hazardous Location | | 2020322315002255 2024322315005860 |
| CML approval | | on request |
| ANZEx | | 18.3018X |
| KCC approval | | |
| Hazardous Location | | |
| Ambient conditions | | |
| Ambient temperature | | -25 ... 100 °C (-13 ... 212 °F) |
| Storage temperature | | -40 ... 100 °C (-40 ... 212 °F) |
| Mechanical specifications | | |
| Connection type | | cable |
| Housing material | | Stainless steel 1.4305 / AISI 303 |
| Sensing face | | PBT |
| Degree of protection | | IP66 / IP67 |
| Cable | | |
| Wire end ferrules | | yes |
| Cable diameter | | 6 mm ± 0.2 mm |
| Bending radius | | > 10 x cable diameter |
| Material | | PVC |
| Color | | blue |
| Number of cores | | 2 |
| Core cross section | | 0.75 mm ² |
| Length | L | 20 m |
| Dimensions | | |
| Length | | 40 mm |
| Diameter | | 30 mm |
| General information | | |

Release date: 2025-06-12 Date of issue: 2025-06-15 Filename: 70133305_eng.pdf

Technical Data

| | |
|---------------------------|--|
| Scope of delivery | 2 self locking nuts in scope of delivery |
| Use in the hazardous area | see instruction manuals |

Connection Assignment

