



Clock

Ex-Time 40

- With Quartz movement
- Sturdy metallic housing
- Simple and uncomplicated time setting

Explosion-protected quartz wall clock



Technical Data

Electrical specifications

Battery type	1x LR14 according to IEC (type-tested)
Operating duration	1 year

Measurement accuracy

Accuracy	-5 / +15 seconds per month
----------	----------------------------

Ambient conditions

Ambient temperature	0 ... 50 °C (32 ... 122 °F)
---------------------	-----------------------------

Mechanical specifications

Mass	approx. 2 kg
Dimensions	400 mm x 60 mm

Data for application in connection with hazardous areas

EU-type examination certificate	PTB 02 ATEX 2197 X
Marking	Ⓜ II 2 G Ex ia IIC T4 Gb

International approvals

SGS approval	
SGS certificate	SGSNA/22/SUW/00077X
SGS marking	Class I, Division 1, Groups A, B, C, D, T4
UKCA approval	
UKCA certificate	CML 21UKEX 21404X
UKCA marking	Ⓜ II 2G Ex ia IIC T4 Gb

General information

Scope of delivery	Ex-Time 40 Batteries Documentation
-------------------	--

Release date: 2022-10-18 Date of issue: 2022-10-18 Filename: 70135099_eng.pdf