

RFID Transponder

IPC11-12 50pcs




- Battery-free data carrier
- 40 bit fixcode free programmable
- Readable and writable from both sides
- Degree of protection IP68
- Packaging unit: 50 pieces

Data carrier



Dimensions



Technical Data

General specifications	
Operating frequency	125 kHz
Transfer rate	2 kBit/s
Memory	
Chip Type	Q5 (Atmel)
EEPROM	40 Bit
Read cycles	unlimited
Directive conformity	
Radio equipment	
Directive 2014/53/EU	EN 300330
RoHS	
Directive 2011/65/EU (RoHS)	IEC/EN 63000
Standard conformity	
Degree of protection	EN 60529
RFID	ISO/IEC 18000-2
Ambient conditions	
Ambient temperature	-25 ... 85 °C (-13 ... 185 °F)

Release date: 2024-06-17 Date of issue: 2024-06-17 Filename: 70144022_eng.pdf

Technical Data

Storage temperature	-40 ... 130 °C (-40 ... 266 °F) for 1000 hours ≤ 150 °C (302 °F) for 24 hours -20 ... 160 °C (-4 ... 320 °F) for 100 x 10 minutes with transposition in 30 seconds
---------------------	--

Mechanical specifications

Degree of protection	IP68
Material	
Housing	PPS and Epoxy (black)
Installation	
In air	yes
Dimensions	
Height	2 mm
Diameter	12.4 mm
Construction type	Cylindrical
Note	Packaging unit, 50-piece

Application

The transponder can be read and written from either side.