



## RFID Transponder


### IQC33-16 50pcs

- Operating frequency 13.56 MHz
- 64 bit Fixcode
- Readable and writable from both sides
- Packaging unit: 50 pieces
- 16 kbit memory available

Data carrier



## Dimensions



## Technical Data

General specifications	
Operating frequency	13.56 MHz
Transfer rate	26 kBit/s
Color	white
Memory	
Chip Type	FRAM MB89R118 (Fujitsu)
FRAM	16 kBit
UID	64 Bit
Memory organization	8 bytes/block
Read cycles	unlimited
Write cycles	unlimited
Data retention period	10 years
Directive conformity	
Radio equipment	
Directive 2014/53/EU	EN 300330
RoHS	
Directive 2011/65/EU (RoHS)	IEC/EN 63000

Release date: 2022-12-15 Date of issue: 2022-12-15 Filename: 70145512\_eng.pdf

## Technical Data

### Standard conformity

Degree of protection	EN 60529
RFID	ISO/IEC 15693-1 ISO/IEC 15693-2 ISO/IEC 15693-3 ISO/IEC 18000-3

### Ambient conditions

Ambient temperature	-25 ... 85 °C (-13 ... 185 °F)
Storage temperature	-40 ... 85 °C (-40 ... 185 °F) 120 °C for 100 h 220 °C for 30 s

### Mechanical specifications

Housing height	2.9 mm ± 0.1 mm
Housing diameter	16 mm ± 0.2 mm
Degree of protection	IP68
Material	
Housing	PPS
Installation	
In air	yes
Mass	1 g
Construction type	Cylindrical
Note	Packaging unit, 50-piece

## Application

The transponder can be read and written from either side.