


Protective mounting bar PGV-PR-PROTECT100



- Mounting aid
- Easily interchangeable

Mounting protection strips for protecting the countersunk profile rails (100 mm) during installation in the floor.

Function

The countersunk profile rails (PGV-PR-GM-*) are installed in the floor, depending on the version. Mounting protection strips can be used to protect the groove of the countersunk profile rails during installation. These strips are glued into the groove of the countersunk profile rails before the rails are glued/cast. After the casting compound/adhesive has hardened, the mounting protection strips can be removed and reused. If required, the metal code bars can then be glued into the clean groove of the countersunk profile rails.

Dimensions



Technical Data

General specifications

Code bar segment	
Nominal segment length	100 mm
Width	30 mm

Ambient conditions

Operating temperature	-40 ... 90 °C (-40 ... 194 °F)
Installation temperature	-40 ... 90 °C (-40 ... 194 °F)
Environmental resistance	UV radiation Humidity

Chemical resistance	Oils Grease Fuels Aliphatic solvents Weak acids
---------------------	---

Mechanical specifications

Material thickness	1 mm
Material	PVC
Mounting type	adhesive
Adhesive	Acrylate-based adhesive
Adhesive strength	4 N / 25 mm

Release date: 2023-02-09 Date of issue: 2023-02-09 Filename: 70162488_eng.pdf