

7500 Series hardware fittings kit

7500-ACC-KIT-01



- CG.NA cable glands and bulkhead fitting for electrical connections with gaskets
- Pneumatic fittings and tubing for manifold connection to enclosure with gaskets
- SEELOK washers for NEMA 4/IP66 panel to enclosure mounting
- Assembly drawing for external and panel mounting
- Can be used with any 7500-MTD-*01 control unit

Accessory kit for mounting, electrical, and pneumatic fittings for 7500-MTD control unit

Function

The 7500-ACC-KIT-01 consists of cable glands for the 7500-MTD control unit with a bulkhead cable gland to get electrical wiring into or out of the enclosure. This bulkhead fitting comes with a gasket for ingress protection to the enclosure. A stopping plug is also included in case one of the cable glands is not used.

Also included is a pneumatic fitting for the manifold, pneumatic bulkhead fitting and gasket for the enclosure, and 3/8" poly tubing for purging and pressurization gas from the 7500-MTD-* manifold to the enclosure. The inlet of the port for the manifold has a 1/2" NPT opening for customer interface.

Reference pressure fittings and assembly are included with the 7500-MTD-* control unit and manifold.

Assembly instructions are included as a quick guide for installation.

Technical Data

General specifications	
Series	7500
System	Type Z Purge ; Ex pzc Purge
Pneumatic parameters	
Maximum pressure	Tube fitting: 0-120 psig Bulkhead fitting: 0-120 psig
Mechanical specifications	
Degree of protection	APM SEELOK 75041 washers: Type 4X and Type 6 enclosure protection
Material	Tube Fitting for Manifold (88000-06-08): Nickel-plated brass Poly Tubing: Polyester base APM SEELOK 75041 washers for mounting screws: 300 series stainless steel and silicone rubber Bulkhead Fitting for Manifold Tubing (88050-06): Nickel-plated brass Bulkhead fitting gasket (WA.FL.M20S): Aramid fibers bonded with NBR
Dimensions	Tube fitting for manifolds (88000-06-08): 1/2" MNPT 0.375" (9.5 mm) Poly Tubing Tube O.D.: 0.375" (9.5 mm) Tube I.D.: 0.25" (6.4 mm) Length: 78" (2 m) APM SEELOK 75041 washers Washer O.D.: 12.7 mm (for M4 thread size) Max thru hole size: 6.35 mm Bulkhead fitting Hole size for enclosure: 20 mm Tube size (for poly): 0.375" (9.5 mm) Bulkhead fitting washer (WA.FL.M20S) O.D.: 23.8 mm I.D.: 20.1 mm Thickness: 1.5 mm
General information	

Release date: 2025-06-18 Date of issue: 2025-06-18 Filename: 70185540_eng.pdf

Technical Data

Scope of delivery

- (2) Cable gland CG.NA.NPT1/2BN.C.16.BR.
 - (1) Stopping plug BP.NA.M16-M20S.PA.GN
 - (1) Cable bulkhead fitting CG.NA.M16.BN.C.16.K01
 - (1) 1/2" to 3/8" Tube fitting for manifold (88000-06-08)
 - 3/8" poly tubing (4 feet)
 - (4) APM SEELOC 75041 mounting washers
 - (4) M4 L=12 mm mounting screws for 7500-MTD
 - (1) WA.FL.M205 washer for pneumatic bulkhead
- Assembly drawing 110-5128(x)