




Adapter for HiD Termination Board HiD-ADP-HiC

- Adapter for mounting a HiC-device to a HiD termination board
- Device is content of an adapter set, consisting of an isolated barrier and an adapter




Function

The device enables the usage of HiC modules on HiD termination boards.
The device consists of an adapter lock and an adapter base.
The device is mounted on the HiD termination board.



Dimensions




Technical Data

Supply		
Rated voltage	U_r	24 V DC , in consideration of rated voltage of used isolated barrier
Electrical specifications		
Connection		see datasheet of isolated barrier
Conformity		
Degree of protection		IEC 60529:2001
Ambient conditions		
Ambient temperature		-20 ... 60 °C (-4 ... 140 °F)
Mechanical specifications		
Degree of protection		IP20
Connection		see datasheet of isolated barrier
Mass		approx. 50 g
Dimensions		18 x 106 x 56 mm (0.7 x 4.2 x 2.2 inch) (W x H x D)
Height		106 mm
Width		18 mm
Depth		56 mm
Mounting		on termination board
General information		
Supplementary information		Observe the certificates, declarations of conformity, instruction manuals, and manuals where applicable. For information see www.pepperl-fuchs.com .

Release date: 2025-04-01 Date of issue: 2025-04-01 Filename: 70188967_eng.pdf

Mounting



Release date: 2025-04-01 Date of issue: 2025-04-01 Filename: 70188967_eng.pdf