



Model Number

KLR-C10-1,25-2,0-K167

Plastic fiber optic - diffuse

Threading M3

Features

- Thread M3
- Coaxial

Series

Fiber optic amplifiers

Device series SU18 ; SU18/35 ; SU19

Description

Attention:

Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.



Accessories

K-LA03

Focusing lens, light spot size approx. 0.5 mm at 8 mm, M3 thread

OMH-LL-M3

Mounting bracket for fiber optic cable, M3 thread

Technical data

General specifications

Sensor range	SU18: 30 mm SU18/35: 100 mm SU19: 30 mm
Fiber optic length	l 2000 mm , adjustable
Fiber optic diameter	d 1.25 mm
Adapter form	00
End piece	thread
Bending radius	min. 15 mm
Fiber configuration	Fv see dimensions
Angle of divergence	67 °
Accessories provided	Cutter for plastic fiber optics

Ambient conditions

Ambient temperature	-55 ... 70 °C (-67 ... 158 °F)
---------------------	--------------------------------

Mechanical specifications

Material	
Optical face	plastic
Sheathing	PVC
Core	plastic
End piece	Stainless steel 1.4305 / AISI 303

Dimensions

