

Display Unit

DPU1200-J2-19S*



- 10 point multi-touch sensor option allows design of modern user interfaces
- Highly robust against cleaning agents and solvents due to seamless glass design
- Optimized design for an easy cleanability
- Low-power consumption and heat dissipation due to LED backlight technology

Display Unit



Function

The DPU1200-J2-19S* display unit is an ATEX/IECEx certified intended for use in Zone 2/22 hazardous areas. Connected to a Pepperl+Fuchs thin client unit or PC unit, the DPU serves as a display with an optional touchscreen. It enables users to perceive the system outputs of the computing unit and to input user data. Five system keys located on the front of the unit allow users to control system functions of the display unit (e. g., brightness control) and the computing unit (e. g., home key). Integrated signal lights on the front keys show selected failure modes in case of a defective component. The display unit is optimized for use with the modular HMI components of the VisuNet GXP product line: TCU1200-* thin client unit, PCU1200-* PC unit, and PSU1200-* power supply unit.

Technical Data

Supply	
Power consumption	average: 22 W at maximum brightness: max. 25 W
Indicators/operating means	
Display	
Type	LC display with LED backlight Optically bonded
Screen size	48.26 cm (19 inch)
Resolution	1280x1024 (SXGA) , Aspect ratio 5:4
Color depth	16.7 Mio.
Contrast ratio	1000:1 (typical)
Brightness	450 cd/m2
Viewing angle	170° horizontal , 160° vertical
Life span	back lamp life: 50.000 hrs typical half life , at 25 °C (77 °F)
Input devices	
Touch screen	optional: projective capacitive, 10 finger multi-touch, glove-friendly
Interface	
Interface type	interface v1.0 from Pepperl+Fuchs for computing units from Pepperl+Fuchs Bluetooth v4.0 , communication distance up to 30 m in open terrain (optional) , transmission power : +8 dBm
Transmitter frequency	2.402 ... 2.48 GHz
Directive conformity	
Electromagnetic compatibility	
Directive 2014/30/EU	EN 61326-1:2013 (industrial locations) non-Bluetooth products only
Radio and telecommunication terminal equipment	
Directive 2014/53/EU	EN 301 328 V2.1.1 EN 301 489-1 V2.1.1 EN 301 489-17 V3.1.1 Bluetooth products only

Release date: 2025-02-17 Date of issue: 2025-02-17 Filename: t187864_eng.pdf

Technical Data

RoHS		
Directive 2011/65/EU (RoHS)		EN 50581:2012-09
Ambient conditions		
Operating temperature		-20 ... 50 °C (-4 ... 122 °F)
Storage temperature		-20 ... 60 °C (-4 ... 140 °F)
Relative humidity		93% at 40°C, non-condensating, according to EN 60068-2-78
Shock resistance		18 shocks 15 g , 11 ms all axis, IEC 60068-2-27
Vibration resistance		10 ... 150 Hz, ± 0.075 mm, 1 G, 10 cycles per axis according to EN60068-2-6
Mechanical specifications		
Degree of protection		IP66 (when mounted on the TCU or PCU from Pepperl+Fuchs)
Material		
Surface		front: glass (optional with stainless steel bezel) Back side: powder coated aluminum
Mass		approx. 11 kg
Dimensions		524 mm x 453 mm x 35 mm
Data for application in connection with hazardous areas		
EU-type examination certificate		BVS 16 ATEX E 081 X
Marking		Ⓜ II 3G Ex ec IIC T4 Gc Ⓜ II 3D Ex tc IIIC T80 °C Dc
Directive conformity		
Directive 2014/34/EU		EN 60079-0:2012+A11:2013, EN 60079-7:2015, EN 60079-31:2014
International approvals		
IECEx approval		IECEx BVS 16.0061X
Approved for		Ex ec IIC T4 Gc Ex tc IIIC T80 °C Dc
Standards		IEC 60079-0:2011, IEC 60079-7:2015, IEC 60079-31:2013

Type Code

Product designation	Protection	Display Size	Screen Type	Interface	Mounting Option	Options & Customization
GXP display unit						
DPU1100-	Display unit (platform: zone 1/21; GXP product group, version 0)					
DPU1200-	Display unit (platform: zone 2/22; GXP product group, version 0)					
Protection						
J1-	IECEX and ATEX II 2 GD; Zone 1/21					
J2-	IECEX & ATEX II (2) 3 GD; Zone 2/22					
Display size						
22F	21.5 inch, Full HD (1920 x 1080 pixel)					
19S	19 inch, SXGA (1280 x 1024 pixel)					
Screen type						
EN-	Anti-glare security glass, no touch					
EC-	Anti-glare security glass, projective capacitive 10 finger multitouch					
Interface						
F1-	5x capacitive system front keys					
F2-	5x capacitive system front keys & Bluetooth interface					
Mounting Option						
NN-	No bezel, prepared for flush mounting					
S1-	Bezel; prepared for panel mounting or into GXP Housing (AG-XX00); Stainless steel AISI 304 (1.4301) (21,5 inch display option only)					
S2-	Bezel; prepared for panel mounting or into EX1 Housing (AG1); Stainless steel AISI 304 (1.4301); (19" Display only)					
Options and customization						
N0	Standard V1.0, no options					
N1	Standard V1.1, no options					

Example: DPU1100-J1-22FEC-F1-S1-N0