



## Field Unit, Stainless Steel

LB9532-T60-B-0A0-00-0

- Standard enclosure for LB-System
- Max. 32 slots for I/O modules
- Installation in Zone 2 or safe area
- Impact resistance enclosure, IP66
- For PROFIBUS DP, PROFIBUS DP V1, PROFINET, and MODBUS RTU
- Image is generic for this device type and may deviate from the specific variant

Field Unit, Stainless Steel



### Function

This field unit is designed to meet the requirements of the most demanding hazardous area and industrial environmental applications.

Brushed stainless steel 316L provides high corrosion and impact resistance at a very wide temperature range.


It is equipped with a base- and an extension backplane.

It provides 32 slots for I/O modules.

The I/O modules can be plugged anywhere on each slot.

The fieldbus and power supply are equipped with non-redundant connections.

## Dimensions



## Technical Data

### General specifications

Installed components	backplane LB9026A , backplane LB9027A
----------------------	---------------------------------------

### Slots

Bus coupler	1
Supply	4
I/O modules (single width)	max. 32
I/O modules (dual width)	max. 16

### Supply

Connection	screw terminals, max. 10 mm <sup>2</sup>
Rated voltage	$U_r$ 24 V DC
Redundancy	no

### Fieldbus connection

Fieldbus type	PROFIBUS DP/DP-V1, PROFINET or MODBUS RTU , depends on bus coupler
Connection	9-pin Sub-D connector (not included with delivery)
Redundancy	no

### Directive conformity

Electromagnetic compatibility	
Directive 2014/30/EU	EN 61439-1:2012 (J.9.2.2 b) , EN 61439-2:2012

### Conformity

Degree of protection	EN 60529
Impact resistance	EN 60079-0

### Ambient conditions

## Technical Data

Ambient temperature	-20 ... 40 °C (-4 ... 104 °F) further on request
Storage temperature	-25 ... 70 °C (-13 ... 158 °F)
Relative humidity	< 75 % (annual mean) < 95 % (30 d/year), no moisture condensation
Shock resistance	shock type I, shock duration 11 ms, shock amplitude 15 g, number of shocks 18
Vibration resistance	frequency range 10 ... 150 Hz; transition frequency: 57.56 Hz, amplitude/acceleration ± 0.075 mm/1 g; 10 cycles frequency range 5 ... 100 Hz; transition frequency: 13.2 Hz amplitude/acceleration ± 1 mm/0.7 g; 90 minutes at each resonance
Impact resistance	7J
<b>Mechanical specifications</b>	
Enclosure cover	hinged door with quarter-turn key locks
Cover seal	foamed silicone
Degree of protection	IP66
Cable entry face B	
M16 quantity	90
M16 series	Cable Glands, Plastic
M16 type	CG.PIDS1.M16.*
M16 clamping range	4 ... 8 mm
M16 info	field signals
M20 quantity	4
M20 series	Cable Glands, Plastic
M20 type	CG.PEDS1.M20.*
M20 clamping range	6 ... 12 mm
M20 info	Fieldbus
M25 quantity	2
M25 series	Cable Glands, Plastic
M25 type	CG.PEDS1.M25.*
M25 clamping range	10 ... 18 mm
M25 info	Power Supply
Material	
Cable gland	Polyamide (PA)
Seal	housing: foamed silicone cable gland: chloroprene
Mass	approx. 25 kg , without modules
Dimensions	
External dimension (A)	600 mm
External dimension (B)	600 mm
External dimension (C)	260 mm
Mounting	4 Mounting bracket for wall mounting included in the scope of delivery
Grounding	M8 internal/external brass nickel-plated grounding bolt
<b>Data for application in connection with hazardous areas</b>	
EU-type examination certificate	
Marking	⊕ II 3(1/2)G Ex eb nA [ia Ga/ib Gb/ic] IIC T4 Gc ⊕ II 3(1/2)D Ex tb [ia Da/ib Db/ic] IIIC T130°C Dc
Certificate	PF 16 CERT 1267 X
Directive conformity	
Directive 2014/34/EU	EN 60079-0:2018 , EN 60079-7:2015 , EN 60079-11:2012 , EN 60079-15:2010 , EN 60079-31:2014
<b>General information</b>	
Ordering information	This device will be delivered completely configured and assembled ready for use. For configuration details please contact Customer Service.
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see <a href="http://www.pepperl-fuchs.com">www.pepperl-fuchs.com</a> .